Amendments to the Specification:

Please replace paragraph [0005] of the published application (No. 2007/0119841) with the following amended paragraph:

[0007]

A welding power supply unit 105 applies the predetermine welding current I and welding voltage V between the welding wire 101 and a base material 107 that is a workpiece through the welding torch 104 and a welding ehip tip 106, thereby to generate an arc 108 and control the wire feeding motor 103.

Please replace paragraph [0021] with the following amended paragraph:

[0021]

Further, the reason $\frac{1}{2}$ why the current I1' is changed to the current I2' is to given energy enough to generate an arc at the short-circuit release time of the time TS3'.

Please replace paragraph [0032] with the following amended paragraph:

[0032]

A torch position command TPC 203 obtained by integrating this torch velocity commence command TVC 201 by an integration element 202.

Please replace paragraph [0033] with the following amended paragraph:

[0033]

In case that the locus is taught the robot manipulator 109, it is general to appoint positions of a start point and an end

Appl. No. 10/582,563 Amdt. Dated June 5, 2009 Reply to Office action of March 5, 2009

point. The reason whey why the position loop 216 is required is that positioning cannot be carried out exactly by only a velocity loop 218.

Please replace paragraph [0140] with the following amended paragraph:

[0140]

A welding power supply unit 5 applies the predetermined welding current I and welding voltage V between the welding wire 1 and a base material 7 that is a workpiece through the welding torch 4 and a welding https://ehep-tip 6 thereby to generate an [[ark]] arc 8, and controls the wire feeding motor 3 to perform welding.

Please replace paragraph [0152] with the following amended paragraph:

[0152]

Further, the reason whey why the current I' is changed to the current I2 is to given energy enough to generate an arc at the short-circuit release time of the time TS3.